

PEDESTAL TYPE ACTUATOR MOUNTING BRACKET FOR 3" & 4" COLONIAL FULL BLOCK® TRUE UNION BALL VALVES

Molded from high impact PVC material, this bracket features a mounting pad with a PCD of 102mm (ISO 5211 F10). The valve and mounting bracket are ordered separately, The bracket can be field-mounted on a Colonial full block TUBV (produced after 2013).

The PVC mounting kit is suitable for use on both PVC and CPVC valves, providing that the atmospheric temperature (on the exterior of the valve) does not exceed 120 degrees. It is designed only for horizontal installation (valve stem / actuator facing UP), not for vertical (valve stem/actuator facing to the side) applications. Maximum allowable weight for actuator: 25 lbs.

Critical dimensions for valve with bracket mounted (in.)

| VALVE SIZE | BRACKET PART NUMBER | А | В | С | D |
|------------|---------------------|-------|------|------|------|
| 3" | V30501P | 10.31 | 5.82 | 5.50 | 7.22 |
| 4" | V40501P | 12.19 | 6.95 | 7.00 | 8.56 |

(Order valve and bracket separately. See list price sheet for valve part numbers.)

| PEDESTAL-TYPE ACTUATOR MOUNT FOR 3" & 4" TUBV | | Colonial ENGINEERING INC. | |
|---|----------|---|--|
| DESIGNED BY | DWG SIZE | COLONIAL ENGINEERING, INC. 6400 Corporate Ave Portage, MI 49002 | |
| EJL | 1 OF 1 | This drawing is the property of Colonial Engineering. It is furnished to you for confidential information purposes only and is not to be disclosed to anyone else or reproduced or used for manufacturing purposes without the express written permission of Colonial Engineering | |
| REVIEWED BY | SCALE - | K11080 | |
| 2-6-17 | INCH | | |